


GROWCOM



SERIAL
DATA PORT
FOR
OPTIONAL
WINDOWS
GROWLINK
PROGRAM

AVAILABLE SENSORS

- ◆ AIR TEMPERATURE ◆ HOT WATER TEMPERATURE ◆ SOIL TEMPERATURE
- ◆ OUTDOOR TEMPERATURE
- ◆ RELATIVE HUMIDITY ◆ OUTDOOR HUMIDITY ◆ SOLAR K-LUX
- ◆ SOLAR PYRANOMETER ◆ SOLAR QUANTUM (PAR) ◆ DIGITAL OVERRIDES


EQUIPMENT CONTROLLED

- ◆ EXHAUST FANS
- ◆ PAD PUMPS
- ◆ EVAPORATIVE COOLERS
- ◆ POSITIVE PRESSURE COOLING
- ◆ MOTORIZED ROOF & SIDE VENTS
- ◆ SHADE & ENERGY CURTAINS
 - ◆ ROLL UP CURTAINS
 - ◆ BLACK OUT CURTAINS
 - ◆ FOG SYSTEMS
- ◆ HORIZONTAL AIR FLOW FANS
 - ◆ FAN JETS
 - ◆ GAS FIRED HEATERS
- ◆ FLOOR HEATING SYSTEMS
- ◆ SOIL HEATING SYSTEMS
- ◆ RADIANT HEATING

GROWCOM SPECIFICATIONS

- | | |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <ul style="list-style-type: none"> ◆ TEMPERATURE ACCURACY - 1° F ◆ HUMIDITY ACCURACY 2% RH ◆ SOLAR LEVEL K-LUX 20% ◆ SOLAR PYRANOMETER 3% ◆ SOLAR QUANTUM (PAR) 3% ◆ TEMPERATURE READOUT CENTIGRADE OR FAHRENHEIT ◆ DIGITAL DISPLAY 16 CHARACTER, 2 LINES ALPHANUMERIC LCD ◆ PROGRAMMING FRONT PANEL TOGGLE SWITCHES ◆ TOTAL SENSOR INPUTS 8 ◆ TOTAL 24 VAC OUTPUTS 12 ◆ TOTAL DIGITAL INPUTS - 4 ◆ OUTPUT SWITCHES ON, CENTER OFF, AUTOMATIC | <ul style="list-style-type: none"> ◆ LIGHTED STATUS INDICATORS HIGH INTENSITY LED ◆ HEATING & COOLING OUTPUTS COMPLETELY PROGRAMMABLE ◆ MAXIMUM VENTILATION STAGES EIGHT STAGES PER SET ◆ DEHUMIDIFICATION CYCLES IMMEDIATE & DELAYED ◆ FOGGING OUTPUT MAINTAINED OR PULSED ◆ MAXIMUM SHADE STAGES EIGHT STAGES PER SET ◆ TIME DELAYS, DIFFERENTIALS, & SEPARATIONS USER SELECTABLE ◆ AVAILABLE MODES DAY, MIDDAY, EVENING, NIGHT, & DIF CAPABLE ◆ ENCLOSURE WEATHERPROOF, CLEAR COVER, LOCKABLE ◆ ENCLOSURE SIZE 8.5" W x 10.5" H x 5.5" D ◆ VOLTAGE INPUT & OUTPUTS 24 VAC, 50/60 Hz |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

GROWCOM



◆ **FEATURE PACKED ENVIRONMENTAL CONTROLLER**

◆ **FOR USE WITH OR WITHOUT YOUR PERSONAL COMPUTER**

◆ **UNIVERSAL LOW VOLTAGE 24 VAC OPERATION**



26111 Ynez Road, C-4 ♦ Temecula, CA 92591 ♦ U.S.A.
 ♦ 951.296.3340 ♦ Fax 951.296.3350
 ♦ www.microgrow.com